





**GAS** II2G Ex d IIC /Ex e II

**DUST** II2D Ex tD A21

**IP66**


**IP66**

**Zone 1 - Zone 21 - Zone 2 - Zone 22**

**-20°C ÷ +40°C**

**-50°C ÷ +80°C**

Materiale : Acciaio zincato  
Materiale : Acciaio inox AISI 304 (Y)  
a richiesta Acciaio inox AISI 316 (YS)  
Material : Galvanized steel  
Material : Stainless steel inox AISI 304 (Y)  
on request Stainless steel inox AISI 316 (YS)



| Codice Code (Gk) | Codice Code (NPT) | Ø     | ØA  | L  |
|------------------|-------------------|-------|-----|----|
| NP 1             | NP 1N             | 1/2   | 14  | 70 |
| NP 2             | NP 2N             | 3/4   | 19  | 70 |
| NP 3             | NP 3N             | 1     | 25  | 60 |
| NP 4             | NP 4N             | 1 1/4 | 31  | 55 |
| NP 5             | NP 5N             | 1 1/2 | 38  | 55 |
| NP 6             | NP 6N             | 2     | 48  | 55 |
| NP 7             | NP 7N             | 2 1/2 | 65  | 68 |
| NP 8             | NP 8N             | 3     | 70  | 68 |
| NP 9             | NP 9N             | 4     | 192 | 68 |

Filettatura conica : protezione IP 66  
utilizzare sigillante Loctite 577  
Taper thread : protection IP 66  
use compound Loctite 577



**GAS** II2G Ex d IIC /Ex e II

**DUST** II2D Ex tD A21

**IP66**


**IP66**

**Zone 1 - Zone 21 - Zone 2 - Zone 22**

**-20°C ÷ +40°C**

**-50°C ÷ +80°C**

Materiale : Acciaio zincato  
Materiale : Acciaio inox AISI 304 (Y)  
a richiesta Acciaio inox AISI 316 (YS)  
Material : Galvanized steel  
Material : Stainless steel inox AISI 304 (Y)  
on request Stainless steel inox AISI 316 (YS)



| Codice Code (Gk) | Codice Code (NPT) | Ø     | L  |
|------------------|-------------------|-------|----|
| EMU 1            | EMU 1N            | 1/2   | 39 |
| EMU 2            | EMU 2N            | 3/4   | 51 |
| EMU 3            | EMU 3N            | 1     | 51 |
| EMU 4            | EMU 4N            | 1 1/4 | 51 |
| EMU 5            | EMU 5N            | 1 1/2 | 51 |
| EMU 6            | EMU 6N            | 2     | 65 |
| EMU 7            | EMU 7N            | 2 1/2 | 65 |
| EMU 8            | EMU 8N            | 3     | 65 |
| EMU 9            | EMU 9N            | 4     | 65 |

Filettatura conica : protezione IP 66  
utilizzare sigillante Loctite 577  
Taper thread : protection IP 66  
use compound Loctite 577



**GAS** II2G Ex d IIC /Ex e II

**DUST** II2D Ex tb IIIC

**IP66**



**IP66**

**Zone 1 - Zone 21 - Zone 2 - Zone 22**

**-20°C ÷ +40°C**

**-50°C ÷ +80°C**

Materiale : Acciaio inox AISI 304 (Y)  
a richiesta Acciaio inox AISI 316 (YS)  
Guarnizione : EPDM (a richiesta Silicone)  
Material : Stainless steel inox AISI 304 (Y)  
on request Stainless steel inox AISI 316 (YS)  
Gasket : EPDM (on request Silicon)



| Codice Code | Ø       | L  |
|-------------|---------|----|
| V 28        | 1/4     | 31 |
| V16         | M16x1.5 | 31 |

Filettatura conica : protezione IP 66  
utilizzare sigillante Loctite 577  
Taper thread : protection IP 66  
use compound Loctite 577